

# Product information

## Battery Clamp Grease

PI 18/03/09/2018



### Description

Battery Clamp Grease is a special grease which is compatible with plastics and is formulated for the maintenance and care of motor vehicle electronic systems, particularly the battery terminals and electrical connectors.

### Properties

- prevents leakage currents
- reduces contact resistance
- good corrosion protection
- very compatible with plastics
- good electronic properties

### Technical data

Brief description	K2G-30 DIN 51502
NLGI number	2 DIN 51818
Color / appearance	rot / red
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	293 °F DIN ISO 2176
Oil separation after 7 days at 104 °F	3,6 % DIN 51817
Oil separation after 18 hours at 104 °F	1,1 % DIN 51817
Flow pressure at -22 °F	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 212 °F	1 a DIN 51811
Behavior in the presence of water	0-40 DIN 51807 Teil 1
Base oil	
Viscosity at 104 °F	32 mm <sup>2</sup> /s ASTM D 7042-04
Flash point	392 °F DIN ISO 2592
Pour point	-6 °F DIN ISO 3016
Density	0,894 g/cm <sup>3</sup>

### Application

Clean contaminated components and treat with Battery Clamp Grease.

### Available pack sizes

50 g Tube plastic	20244
	GB-F-E-USA-CAN

**Our information is based on thorough research and may be considered reliable, although not legally binding.**



### Areas of application

Used especially for battery terminals, connections and plug connectors in vehicle electronic system.